

GRAYLING INDUSTRIES, INC.
MATERIAL SAFETY DATA SHEET – CONTROL LOW ODOR MASTIC REMOVER

This Material Safety Data Sheet (MSDS) conforms to the requirements of ANSI Z400.1.
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this MSDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY

Product Name: **CONTROL LOW ODOR MASTIC REMOVER**

Item Number: 19105

MANUFACTURER:

Grayling Industries, Inc.

1008 Branch Drive

Alpharetta, GA 30004

Date Prepared: March 1, 2010

Date Superseded: July 10, 2006

EMERGENCY PHONE NUMBER:

1.800.535.5053 (Infotrac)

INFORMATION: 1.800.635.1551

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

	<u>CAS Number</u>
Medium Aliphatic Solvent Distillates	64742-88-7
2-Butoxyethanol	111-76-2
Heavy Aromatic Solvent Naphtha	64742-94-5
NonYlphenol Ethoxylate	9016-45-9

SECTION 3. HAZARDS IDENTIFICATION

RISK STATEMENTS:

R 65 Harmful: may cause lung damage if swallowed

R36 / 37/ 38 Irritating to eyes, respiratory system and skin.

R20 / 65 Harmful by inhalation, may cause lung damage if swallowed.

SAFETY STATEMENTS:

S24 / 25 Avoid contact with skin and eyes.

SECTION 4. FIRST AID MEASURES

Eye Contact:

For Eyes, flush with plenty of water for 15 minutes and get medical attention.

Skin Contact:

In case of contact with skin immediately remove contaminated clothing. Wash skin thoroughly with soap and water. Wash contaminated clothing before reuse.

Inhalation:

After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen.

If breathing has stopped give artificial respiration. **CALL A PHYSICIAN IMMEDIATELY!**

Swallowing:

If swallowed, **CALL A PHYSICIAN IMMEDIATELY! DO NOT INDUCE VOMITING!**

Have patient lie down and keep warm. Vomiting may lead to pneumonitis, which may be fatal.

SECTION 5. FIRE FIGHTING MEASURES

Extinguishing Media:

NFPA Class B extinguishers (Carbon Dioxide or foam) for class IIIA liquid fires.

Special Fire Fighting Procedures:

Water spray may be ineffective on fire, but can protect fire-fighters and cool closed containers.

Use fog nozzles if water is used.

Do Not Enter Confined Fire-Space without full bunker gear.

(Helmet with face shield, bunker coats, gloves, and rubber boots).

Use NIOSH approved positive-pressure self-contained breathing apparatus.

Unusual Explosion and Fire Procedures:

COMBUSTIBLE !

Keep Container tightly closed.

Isolate from oxidizers, Heat, and open flame.

Closed containers may explode if exposed to extreme heat.

Applying to hot surfaces requires special precautions.

Empty container very Hazardous! Continue all label precautions!

SECTION 6. ACCIDENTAL RELEASE MEASURES

Containment Techniques:

Keep unprotected personnel away. Stop spill at source. Dike area and contain.

Clean-Up Procedures:

Clean up remainder with absorbent material. Mop up and dispose of material.

SECTION 7. HANDLING AND STORAGE

Handling:

Isolate from oxidizers, heat, and open flame.

Use only with adequate ventilation. Avoid breathing of vapor or spray mist.

Do not get in eyes, on skin, or on clothing.

Wear OSHA Standard Goggles or face shield. Consult Safety Equipment Supplier.

Wear gloves, apron, and footwear impervious to this material. Wash clothing before reuse.

Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, braze, or weld.

Empty container very hazardous! Continue all label precautions!

Storage:

Store large amounts in structures made for OSHA Class IIIA liquids.

Keep container tightly closed and upright when not in use to prevent leakage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory Exposure Controls

A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION continued

Ventilation:

Local Exhaust	: Necessary
Mechanical (General)	: Acceptable
Special	: None
Other	: None

Personal Protection

Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier.

Wear gloves, apron, and footwear impervious to this material.

Wash clothing before reuse.

Work and Hygienic Practices

Provide readily accessible eye wash stations and safety showers.

Wash at end of each work shift and before eating, smoking, or using the toilet.

Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles,

Launder or discard contaminated clothing.

SECTION 9. PHYSICAL DATA

Appearance:	Liquid, Water-White
Odor:	Aromatic
Boiling Point:	174° 190° 196°* C / 346° 375° 385°* F (*=End Point)
Auto Ignition Temperature:	260° C / 500° F (Lowest Component)
Lower Flammable Limit In Air (% by vol):	0.9
Flash Point (Test Method)	60° C / 141° F (TCC) (Lowest Component)
Flammability Classification:	Class IIIA
Gravity @ 68/68° F / 20/20° C:	
API:	43.9
Specific Gravity (Water=1) :	0.807
Pounds/Gallon:	6.719
VOC'S (>0.44 lbs/Sq.Inch)	0.0 Vol. % / 0.0 g/L / 0.000 Lbs/Gal
TOTAL VOC's (TVOC):	99.0 Vol. % / 796.1 g/L / 6.631 Lbs/Gal
Nonexempt VOC's (CVOC):	99.0 Vol. % / 796.1 g/L / 6.631 Lbs/Gal
Hazardous Air Pollutants (HAPS):	0.0 Wt. %/ 0.0 g/L / 0.000 Lbs/Gal
Vapor Pressure (mm of Hg) @20° C	0.5
Nonexempt VOC Partial Pressure (mm of Hg @ 20° C)	0.5
Vapor Density (air=1) :	5.0
Water Absorption:	Appreciable
Refractive Index:	1.438
Mixed Aniline Point (Acid Insol):	63° C / 147° F

SECTION 10. STABILITY AND REACTIVITY

Stability:

Stable under normal conditions.

Conditions to Avoid:

Isolate from oxidizers, heat, and open flame.

Materials to Avoid:

Isolate from strong oxidizers such as permanganates, chromates, and peroxides.

Hazardous Decomposition Products:

Carbon Monoxide, Carbon Dioxide from burning.

Hazardous Polymerization:

Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

MATERIAL	CAS#	TWA (OSHA)	TLV (ACGIH)	HAP
Medium Aliphatic Solvent Naphtha	*64742-88-7	5 mg/m ³	5 mg/m ³	NO
2-Butoxyethanol	111-76-2	50 ppm S	20 ppm S	NO
Heavy Aromatic Solvent Naphtha	*64742-94-5	100 ppm	5 mp/m ³	NO
Nonylphenol Ethoxylate	9016-45-9	None Known	None Known	NO

This product contains no EPQ Hazardous Air pollutants (HAP) in amounts > 0.1%.

Using manufacturers' data, based on EPA Method 311, the following EPA Hazardous Air Pollutants may be present in trace amounts (less than 0.1%):

Cumene, Naphthalene

MATERIAL	CAS#	CEILING	STEL (OSHA/ACGIH)
		None Known	None Known

ACUTE HAZARDS

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.

Absorption thru skin increases exposure.

Primary irritation to eyes, redness, tearing, blurred vision.

Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

Breathing vapor can cause irritation.

Acute overexposure can cause damage to kidneys, blood, nerves, liver & lungs.

SWALLOWING:

Harmful or fatal if swallowed.

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

SECTION 11. TOXICOLOGICAL INFORMATION continued

SUBCHRONIC HAZARDS / CONDITIONS AGGREGATED

CONDITIONS AGGREGATED:

Chronic overexposure can cause damage to kidneys, blood, nerves, liver & lungs.
Persons with severe skin, liver, or kidney problems should avoid use.

CHRONIC HAZARDS

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

Lung, liver tumors have been reported in laboratory mice.
Leukemia has been reported in humans from Benzene.
This product contains less than 1 ppm of Benzene.
Not considered hazardous in such low concentrations.
Absorption thru skin may be harmful.

SECTION 12. ECOLOGICAL INFORMATION

MAMMALIAN INFORMATION:

MATERIAL	CAS #	LOWEST KNOWN LETHAL DOSE DATA
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LD50 (ORAL) 320.0 mg/kg (Rabbits)
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LD50 (VAPORS) 700 ppm (Mice)
Ethylene Glycol Butyl Ether	111-76-2	LOWEST KNOWN LD50 (SKIN) 440.0 mg/kg (Rabbits)

AQUATIC ANIMAL INFORMATION:

The most sensitive known aquatic group to any component of this product is:
Tidewater Silversides 1250 ppm or mg/L (96 hour exposure).
Keep out of sewers and natural water supplies.

MOBILITY:

This material is a mobile liquid.

DEGRADABILITY:

This product is partially biodegradable.

ACCUMULATION:

Bioaccumulation of this product has not been determined.

SECTION 13. DISPOSAL CONSIDERATION

Recycle / dispose of, observing national, regional, state, provincial and local health, safety and pollution laws.

If questions exist, contact the appropriate agencies.

SECTION 14. TRANSPORT INFORMATION

DOT SHIPPING NAME: BULK: Compounds, Cleaning Liquid
(Medium Aliphatic Solvent Naphtha, 2-Butoxyethanol)
Combustible liquid, NA1993, PG-III
Combustible liquid. Not DOT regulated on trucks in containers of < 119 gallons.

DRUM LABEL: None (Combustible Liquid)
IATA / ICAO: None
IMO / IMDG: None

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

SECTION 15. REGULATORY INFORMATION

EPA REGULATION:

SARA SECTION 311/312 HAZARDS: Acute Health, Chronic Health, Fire

All components of this product are on the TSCA list.

SARA Title III Section 313 Supplier Notification

This product contains the indicated <*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDS's that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS #	WT. % (REG.SECTION)	RQ (LBS)
*2-Butoxyethanol	111-76-2	11 (313)	None

INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries: Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 2, HEALTH (HMIS): 3, FLAMMABILITY: 2, REACTIVITY: 0
This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING:

Employees should be made aware of all hazards of this material (as stated in this MSDS) before handling it.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications.

All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.

* * *

011601_BG_S0028-R1