

Hazard rating: HMIS
HEALTH 1 FLAMMABILITY 2
REACTIVITY 0
PERSONAL
PROTECTION H

MATERIAL SAFETY DATA SHEET

SECTION 1

PRODUCT IDENTIFICATION

NAME

AMR-160 High Performance Mastic Remover

24 HOUR EMERGENCY RESPONSE NUMBER 1-866-359-5661

Distributed By:

Abatix Environmental Corp. 8311 Eastpoint Drive #400

Dallas, TX 75227 (214) 381-1146

SECTION 2

HAZARD IDENTIFICATION

NAME

CAS #EXPOSURE GUIDELINES

PETROLEUM DISTILLATES

64742-47-8

100 PPM (525 mg/m3) is a recommended PEL for 8-hour TWA

AROMATIC HYDROCARBON

64742-94-5

100 PPM Total Hydrocarbons

NAPHTHALENE *

91-20-3

10 PPM (50 mg/m3) 1-3 % by weight

ETHYLENE GLYCOL MONOBUTYL ETHER *

111-76-2

25 PPM (SKIN) 1-3% by weight

* Subject to the reporting requirements of SARA 313 and 40 CFR 372:

SECTION 3

PHYSICAL DATA

BOILING POINT (F)

370-500

VAPOR DENSITY Heavier than air

VAPOR PRESSURE (mm Hg)

Negligible

EVAPORATION RATE Slower than ether

ODOR

Solvent/Moderate

WEIGHT PER GALLON 7.00

% VOLATILE

100

APPEARANCE Clear

SECTION 4

- FIRE AND EXPLOSION HAZARD

FLASH POINT (METHOD USED)

145 degrees F. Method PMCC Note: Minimum

421 degrees F. Note Approximate

AUTO IGNITION TEMPERATURE

EXTINGUISHING MEDIA Small fires: Extinguish with dry chemical, CO2 or foam. Large fires: The use of dry chemical or foam is recommended.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS The use of SCBA is recommended for fire fighters. Water spray may be useful in minimizing vapors and cooling containers exposed to heat and flame. Avoid spreading burning liquid with water used for cooling purposes.

UNUSUAL FIRE AND EXPLOSION

This material is a NFPA IIIA combustible liquid.

SECTION 5 HEALTH HAZARD INFORMATION/FIRST AID

EYE CONTACT Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, seek medical attention.

SKIN Flush skin with plenty of water; use soap if available. Remove contaminated clothing. Call a physician if irritation persists. Wash clothing before reuse.

INHALATION Remove to fresh air. If breathing has stopped, administer artificial respiration. Keep at rest. Get prompt medical attention.

INGESTION If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

ASPIRATION HAZARD This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

THIS MATERIAL HAS NOT BEEN IDENTIFIED AS A CARCINOGEN OR PROBABLE CARCINOGEN BY NTP, IARC, OR OSHA.

SECTION 6 HEALTH HAZARDS/ROUTES OF ENTRY

EYE CONTACT Direct contact with this liquid may cause irritation. Exposure to it's vapors may cause burning tearing or redness.

SKIN CONTACT Repeated or prolonged contact with liquid may cause irritation, reddening and dermatitis.

INHALATION High vapor concentrations may cause headaches, stupor, irritation of throat and kidney effects. Extreme aspiration into the lungs may cause pneumonia or death.

INGESTION This material causes irritation of the stomach and intestines and signs of nervous system depression

Acute exposure may result in narcosis, pulmonary edema and severe kidney and liver damage.

SECTION 7 SPECIAL PROTECTION INFORMATION

VENTILATION Air contaminant levels should be controlled below the PEL or TLV for this product. (See Section 2) Mechanical ventilation may be necessary if working with this product in enclosed areas.

RESPIRATORY PROTECTION Respiratory protection may be necessary to minimize exposure to organic vapors. Use NIOSH approved organic vapor air purifying respirator, self contained breathing apparatus, or air supplied respirators dependent on concentration.

PROTECTIVE GLOVES The use of impermeable gloves (Nitril or Neoprene) is recommended to prevent contact and possible irritation.

EYE PROTECTION When contact with liquid is possible, use a face shield, otherwise use safety glasses or goggles.

PROTECTIVE EQUIPMENT It is suggested that a clean source of water is available in the work area for flushing eyes and skin. Impervious clothing should be worn as needed.

SECTION 8

REACTIVITY DATA

STABILITY : Stable

HAZARDOUS POLYMERIZATION : Will not occur.

INCOMPATIBILITY: Strong

oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide.

SECTION 9 SPILL OR LEAK PROCEDURES

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. If spill is indoors, ventilate area of spill. Foam, especially high expansion foam, may be used to suppress vapors. Keep contained and dispose of in accordance with local, county, state and federal regulations.

SECTION 10 SHIPPING INFORMATION

DOT PROPER SHIPPING NAME: Combustible Liquid, n.o.s.

DOT HAZARD CLASS: Combustible Liquid

DOT IDENTIFICATION NUMBER: NA 1993 (not regulated in pkg. of less than 119 gal.)

PACKING GROUP: III

SECTION 11

STORAGE AND SPECIAL PRECAUTIONS

Keep containers tightly closed. Keep containers cool, dry, and away from sources of ignition. Avoid inhalation of vapors. Do not pressurize, cut weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. "Empty" Drums should be completely drained, properly bunged and properly shipped to a qualified drum reconditioner.

SECTION 12

DOCUMENTARY INFORMATION

The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or is to be implied regarding the accuracy or completeness of this information, the results to be obtained from the use of this information or the product, the safety of this product or the hazards related to its use. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition that he assume the risk of his use thereof.