



While not primary fire protection gear, KLEENGUARD\* A65 Coveralls are designed to be worn in areas where exposure to sparks is possible.

### Typical Uses

- Welding
- Oil refining
- Utilities
- Grinding

Comfortable, breathable and durable fabric resists tearing

Complies with the flame resistance requirements cited by paragraph 6.1 of CAN/CGSB-155.20-2000

Flame resistant compliant per NFPA 701 FLAME PROPAGATION TEST (1989 edition)

NFPA 99 compliant antistatic material

Design meets the ANSI/ISEA 101-1996 sizing standard



### KLEENGUARD\* A65 Apparel Fabric Properties

Physical Properties	Test Method	Results
Flammability	NFPA 701	Pass
	CAN/CGSB-155.20-2000	Complies
Mullen Burst	ASTM E96-80	30 psi
Tensile Strength (MD)	ASTM D5034	19.1 lbs
		(CD)
Antistat	NFPA 99	Pass
Comfort Properties	Test Method	Results
Air Permeability	ASTM D737	57.9 cfm
Moisture Vapor Transport Rate	ASTM E96	5000 g/m <sup>2</sup> /24 hrs

### Coveralls

Zipper front			Zipper front, elastic wrists, ankles & hood			Zipper front, elastic wrists, ankles, hood & boots		
Stock Code	Size	Case Count	Stock Code	Size	Case Count	Stock Code	Size	Case Count
45312	M	25	45322	M	25	45352	M	25
45313	L	25	45323	L	25	45353	L	25
45314	XL	25	45324	XL	25	45354	XL	25
45315	XXL	25	45325	XXL	25	45355	XXL	25
45316	XXXL	21	45326	XXXL	21	45356	XXXL	21
45317	XXXXL	21	45327	XXXXL	21	45357	XXXXL	21

