



Dry Moly Lube, 11 Wt Oz

No. 03084 | Item# 1003351 | Case# 1003350

Product Description	Lowers friction, prevents galling and helps to reduce torque and energy consumption. High anti-friction and anti-seizure properties. Fast drying film resists dirt and dust build-up.
Applications	Gaskets, transfer belts, conveyor belts, motors, plant machinery and handling equipment, rubber moldings, high temperature, low load, or high rpm slides, rollers, wheels, gears, chains & hoists
Unit Package Description	16 Ounce Aerosol
Brand	CRC
Generic Description 1	Dry Film Lubricant
Net Fill	11 Wt Oz
UPC Code	078254030845
Unit Dimensions	7.75H x 2.63W x 2.63D in
Units Per Case	12
Case Dimensions	8.6H x 8.4W x 11.3D in
Cases Per Pallet	133
Case Weight	12 lbs
I 2 of 5 Code	30078254030846
Appearance	Dark Gray Viscous Liquid
Base Type	Molybdenum Disulfide
Flash point (F)	-20°F
Flash point (C)	-29°C
Flammability Class - CPSC	Extremely Flammable
Spec Gravity Concentrate	0.71
Plastic Safe	No
Film Type	Dry
Evaporation Rate	Fast
Working Temp (F)	650°F (Continuous) / 750°F (Intermittent)
Working Temp (C)	343.3°C (Continuous) 398.9°C (Intermittent)

Last revised: 9/20/2019
Page 1 of 2





Propellant	Hydrocarbon
Aerosol Flammability Level	III
DOT Proper Shipping Name	Aerosols, Flammable, Limited Quantity
VOC % (Consumer Product def)	61.8
VOC g/L (Consumer Product def)	438.78
VOC lbs/gal (Consumer Prod def)	3.66
VOC Category	Dry Film Lubricant
Removal (How To)	Remove with a heavy duty degreaser.