



Manufacturing Equipment for Abatement
and Restoration Industry Since 1988

OA2200C HEPA Air Filtration Machine

OmniAire 2200C is a construction grade negative air machine with two speeds, powerful blower and full size, 12" deep HEPA filter. This is a well constructed and reliable air scrubber with many accessories to remove airborne particulates and bio-contaminants. Equipped with a 99.97% HEPA filter and 2-stage pre-filter, it is used on asbestos, lead and mold abatement projects. The HEPA filter can be replaced with an economical Bag Filter with high capacity to collect bulk dust from cutting or grinding of concrete, wood or plaster. For VOCs and odor control, activated carbon filters can be quickly installed.



OmniAire 2200C SPECIFICATIONS

- Airflow Ratings (cfm)*** 1000 & 2000
- Operating Speeds** 2 Speeds
- Filtration Stages** - HEPA Filter 99.97%, 0.3µ
 - MERV 8 primary/secondary filter
- Optional** - OdorGuard600 activated carbon filter
 - 9-Packet Bag Filter, MERV14
- Recessed Controls** with: LOW/OFF/HIGH speed switch
 - ... CHANGE FILTER Indicator Light
- Motor** 1.5 hp with Thermal Overload
- Circuit Requirements**** 115V 60Hz 13.8 amps
- Cabinetry** Aluminum, silicone sealed before riveting
- Exhaust Collar** 12"
- Carrying Handles w/Rubber Grips** 4
- 5" Casters** 2 Fixed, 2 Swivel
- Weight with Filters** 140 lbs
- Dimensions** 35"L x 26"W x 31"H

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.

ORDERING INFO	PART #
OmniAire 2200C	OA2200C
HEPA Filter 99.97%, 0.3µ	OAH2424L
Primary/Secondary Filter (qty 20)	OAP2424
Intake Manifold, 12"	OAIM2200-12
Carbon Vapor Trap Filter	OCVT2424
OdorGuard 600 Carbon Filter	OG2424
Bag Filter Housing	HBF2200
Bag Filter, MERV14	OBF10
Flexible Duct, 12" x 25'	OAD12

Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

Omnitec Design, Inc.

4640 Campus Place, Suite 110 Mukilteo, WA 98275
Visit us @ www.omnitecdesign.com
Office: 425-290-3922