



ST0306A

STEEL ROLLING TOWER SCAFFOLDS

- 1,000 LBS. LOAD CAPACITY
- ONE PERSON ASSEMBLY!
- FITS THROUGH 30" DOOR FRAME
- LOCKING PINS PREVENT ACCIDENTAL UNLOCKING
- DECK PIN SECURES PLATFORM

END-FRAMES:

Full height unit 29" wide x 65" high (without casters)
Half unit 29" wide x 35-1/2" high (without casters)

WIDTH (ASSEMBLED):

29-1/2" with casters
66-3/4" with outriggers and casters

PLATFORM:

Exterior grade, edge protected 5/8" thick plywood
6 ft. unit – 28.75" wide x 67" long

PLATFORM HEIGHT (MAX): with casters

6 ft. unit – 6'
12 ft. unit – 11' 5"
15 ft. unit – 14' 5"



ST0606A



PART NO.	SIZE	APPROX. WEIGHT
	H x L	
ST0306A*	3 ft. x 6 ft.	115 lbs
ST0606A	6 ft. x 6 ft.	132 lbs.

*Does NOT include casters

Part No. PK734A, 5" caster w/ hardware.

Part No. PK735A, Outrigger (does not include casters; requires 4 of #PK734A).

Part No. PK736A, 39" handrail.

TO MAKE A 12 FT. TOWER, YOU NEED:

- (2) #ST0606A - 6' Scaffold
- (1) #PK735A - Outriggers
- (1) #PK736A - Handrail
- (4) #PK734A - Casters

TO MAKE A 15 FT. TOWER, YOU NEED:

- (2) #ST0606A - 6' Scaffold
- (1) #ST0306A - 3' Scaffold
- (1) #PK735A - Outriggers
- (1) #PK736A - Handrail
- (4) #PK734A - Casters



Mobile work stand with 2 way casters, with locks. This product has the ability to fold for storage and transportation.

- Fits through 30" door frame
- Locking pins prevent accidental unlocking
- Deck pin secures platform



Mobile Work Stand

MINI FORTRUSS® MOBILE WORK STAND

- Centre locking hinge.
- Two-way casters.
- Exclusive steel wrap weld connection.
- Premium powder paint.
- Folds flat for easy storage.

Part No.	Casters	Weight	Overall Length W/ Casters	Overall Height W/ Casters	Overall Width	Folded Unit Width	Plank Width	Plank Length	Plank Height Adjustable	Load Rating
SM1404A	4	68	47½"	50¼"	22½"	6¼"	8.5" (2) 17" overall	46-5/16"	12", 24", 36", 48"	500 lbs.