

# FIBERGLASS 375 lbs. TYPE IAA load capacity\*

## PLATFORM LADDER FP1100HD SERIES

# FIBERGLASS 375 lbs. TYPE IAA load capacity\*

## PLATFORM LADDER FP1400HD SERIES



FP1104HD

**SHOX**

**IMPROVED PLATFORM DESIGN!**

Gapless and slimmer for improved storage.



FP1404HD

**SHOX**

**IMPROVED PLATFORM DESIGN!**

Gapless and slimmer for improved storage.

- SHOX™ - superior impact absorption**
- Full Metal Boot™**
- Top rail guard**
- Gapless slip-resistant platform**
- Double-rivet step construction**
- Heavy duty gusset bracing**

- SHOX™ - superior impact absorption**
- Da Boot™ Patent # 7,000,731 B2**
- Top rail guard**
- Gapless slip-resistant platform**
- Heavy duty gusset bracing**
- Riveted step construction**

MODEL	HT. TO PLATFORM	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FP1104HD	3' 9"	3"	24 3/8"	45 1/8"	25	5.4'
FP1106HD	5' 8"	3"	27 5/16"	52 3/8"	36	7.8'
FP1108HD	7' 7"	3"	30 1/4"	65"	49	10.4'
FP1110HD*	9' 6"	3"	33 5/16"	75 1/2"	61	13'
FP1112HD*	11' 5"	3"	36 1/4"	87 1/2"	73	15.6'

MODEL	HT. TO PLATFORM	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FP1403HD	2' 10"	3"	23 5/16"	34 1/4"	20	3.9'
FP1404HD	3' 9"	3"	24 13/16"	39 7/8"	22	5.2'
FP1405HD	4' 9"	3"	26 3/16"	45 3/4"	25	6.5'
FP1406HD	5' 8"	3"	27 3/4"	52"	28	7.6'
FP1408HD	7' 7"	3"	30 7/8"	63 3/4"	42	10.2'
FP1410HD*	9' 6"	3"	33 13/16"	75 9/16"	58	12.7'
FP1412HD*	11' 5"	3"	36 13/16"	86 5/8"	69	15.3'



**ANSI**  
Meets or exceeds requirements of American National Standards Institute  
ANSI A14.5



FEATURING THE EXCLUSIVE  
**FULL METAL BOOT™**

\*Special duty: manufacturer tested to 375 lbs.



**ANSI**  
Meets or exceeds requirements of American National Standards Institute  
ANSI A14.5



**BRUTE** 375



\*Special duty: manufacturer tested to 375 lbs.